

Velmex Encoder Selection

Rotary Encoder Selection for UniSlides®, BiSlides®, XSlide™ and Rotary Tables

Linear Assemblies					
	Encoder CPR --->	100	200	400	500
	(Counts Per Revolution)				
Leadscrew Code		Encoder Resolution** (inches/mm)			
C / P40	0.0025 in/rev	0.000025	0.0000125	0.000006	0.000005
	mm/rev	0.000635	0.0003175	0.000152	0.000127
B / P20	0.050 in/rev	0.000500	0.000250	0.000125	0.000100
		0.012700	0.006350	0.003175	0.002540
W1 / P10 / E01	0.100 in/rev	0.001000	0.000500	0.000250	0.000200
		0.025400	0.012700	0.006350	0.005080
W2 / P5	0.200 in/rev	0.002000	0.001000	0.000500	0.000400
		0.050800	0.025400	0.012700	0.010160
W4 / P2.5 / E04	0.400 in/rev	0.004000	0.002000	0.001000	0.000800
		0.101600	0.050800	0.025400	0.020320
K1 / Q1 / M01	1.00 mm/rev	0.010000	0.005000	0.002500	0.002000
	in/rev	0.000394	0.000197	0.000098	0.000079
K2 / Q2 / M02	2.00 mm/rev	0.020000	0.010000	0.005000	0.004000
	in/rev	0.000787	0.000394	0.000196	0.000157
	Encoder CPR --->	100	200	400	500
Rotary Tables	(Counts Per Revolution)				
Model		Encoder Resolution (in degrees)			
B4818TS	20 deg/turn*	0.200000	0.100000	0.050000	0.040000
B4836TS	10 deg/turn*	0.100000	0.050000	0.025000	0.020000
B4872TS	5 deg/turn*	0.050000	0.025000	0.012500	0.010000
B5990TS	4 deg/turn*	0.040000	0.020000	0.010000	0.008000
* deg/turn of input shaft					
*Suggested Encoder Resolution in BOLD Type					



Positioning Systems for Science and Industry

Velmex, Inc.
7550 State Routes 5 & 20
Bloomfield, NY 14469-9389

TF: 1.800.642.6446
P: +1.585.657.6151
F: +1.585.657.6153

www.velmex.com
info@velmex.com